



1301
09

ES DECLARATION OF CONFORMITY

according to Council Directive No. 89/106/EHS, as amended by
Council Directive No. 93/68/EHS

Manufacturer: KRPA DEHTOCHEMA, a.s. with its registered seat Svoboda nad
Úpou,
Nádražní 450, District of Trutnov, Zip Code: 542 24,
herewith declares and confirms under its own responsibility
that the following product:

Bitagit 40 Mineral

V 60 S 40

according to requirements of ČSN EN 13 707 and ČSN EN 13 969
represents a water-proofing band from oxidized bitumen with a glass-fiber mat inlay and with
surfacing performed by means of mineral fine-grain spreading.

Feature and Application:

The Bitagit 40 Mineral in band form is intended for multi-layer roof insulation:

- separately in water-proofing coatings which are not subjected to tension forces
- in combination with bands of great tensile stress resistances
- in addition to, it is used for ground humidity insulation of substructures and of gravitational moisture

Band Composition

- | | |
|----------------------|-------------------------------|
| - upper side | fine grain spreading |
| - bitumen substance | oxidized bitumen with fillers |
| - supporting inlay | glass-fiber mat |
| - bitumen substance | oxidized bitumen with fillers |
| - bottom performance | PE - film |

Wrapping:

- solid paper wrapping or special tapes
- products shall be supplied on a palette unit of 800 x 1200 mm and they are secured by means of the PE film

Transport and Storage:

Rolls shall be transported and stored on one layer and in vertical position (i.e. with their axes perpendicularly to a floor). Protect from direct sunshine.

Processing : Basic – smelting by flame

We recommend bands' application under air temperature at least 10°C

Guarantee: 3 years

