



1301
09

ES DECLARATION OF CONFORMITY

**according to Council Directive No. 89/106/EHS, as amended by
Council Directive No. 93/68/EHS**

Manufacturer: KRPA DEHTOCHEMA, a.s. with its registered seat Svoboda nad
Úpou,
Nádražní 450, District of Trutnov, Zip Code: 542 24,
**herewith declares and confirms under its own responsibility
that the following product:**

Sklobit 40 Dekor

G 200 S 40

according to requirements of ČSN EN 13 707

represents a water-proofing band from oxidized bitumen with a glass fiber inlay and with surfacing performed by means of color coarse-grained spreading. On upside there are edges of 8 – 10 cm width performed by reason of overlapping and connecting of bands by means of smelting.

Feature and Application:

The Sklobit 40 Dekor is intended as a basic version of final layers of water-proof roof band complex. This layer complex shall be performed from oxidized bitumen bands.

The bands shall be applied by means of smelting or by mechanical anchorage to a suitable groundwork.

Band Composition:

- | | |
|----------------------|--------------------------------|
| - upper side | color coarse-grained spreading |
| - bitumen substance | oxidized bitumen with fillers |
| - supporting inlay | glass fabric |
| - bitumen substance | oxidized bitumen with fillers |
| - bottom performance | PE film |

Wrapping:

- solid paper wrapping or special tapes
- products shall be supplied on a palette unit of 800 x 1200 mm and they are secured by means of the PE film

Transport and Storage:

Rolls shall be transported and stored on one layer and in vertical position (i.e. with their axes perpendicularly to a floor). Protect from direct sunshine.

Processing : Basic – smelting by flame

We recommend bands' application under air temperature at least 10°C

Guarantee: 3 years

