



1301
09

ES DECLARATION OF CONFORMITY

according to Council Directive No. 89/106/EHS, as amended by
Council Directive No. 93/68/EHS

Manufacturer: KRPA DEHTOCHEMA, a.s. with its registered seat Svoboda nad
Úpou,
Nádražní 450, District of Trutnov, Zip Code: 542 24,
**herewith declares and confirms under its own responsibility
that the following product:**

Bitagit R

V 13

**according to requirements of ČSN EN 13 707 and ČSN EN 13 969
represents a water-proofing band from oxidized bitumen with a glass-fiber mat inlay and with
double-sided surfacing performed by means of mineral fine-grain spreading.**

Feature and Application:

The Bitagit R is intended for sub-grade and securing insulation under composed roof covers, especially under bitumen shingles.

In addition to, the band is suitable for ground humidity insulation of substructures, for temporary insulation measures or as a supplementary insulation layer.

Band Composition

- upper side	fine grain spreading
- bitumen substance	oxidized bitumen with fillers
- supporting inlay	glass-fiber mat
- bitumen substance	oxidized bitumen with fillers
- bottom performance	fine grain spreading

Wrapping:

- solid paper wrapping or special tapes
- products shall be supplied on a palette unit of 800 x 1200 mm and they are secured by means of the PE film

Transport and Storage:

Rolls shall be transported and stored on one layer and in vertical position (i.e. with their axes perpendicularly to a floor). Protect from direct sunshine.

Application: free laying

We recommend bands' application under air temperature at least 10°C

Guarantee: 2 years

